

TECHNICAL DATA SHEET

**REACTION TIME**

approx. 30 min.

**APPLICATION FIELD**

for use in all water cooled, closed cooling systems

**CONSUMPTION**

30 ml per 1 L

**APPLICATION INTERVAL**

before every change of coolant

RADIATOR PURIFIER KÜHLSYSTEMREINIGER

COOLING SYSTEM

**APPLICATION**

1) Add the product to the cooling system before exchanging the coolant. 2) Move all heater controls to "hot". 3) Let the engine idle for approx. 30 minutes. 4) Drain system completely and flush with clean water. 5) Refill the cooling system following the manufacturer's instructions. Sufficient for cooling systems up to 10 L capacity.

Attention: Open radiator filling port slowly and successively – risk of burning!

DESCRIPTION

Radiator Purifier for use in all water cooled, closed cooling systems (commercial vehicles, passenger cars, industrial heat exchangers). Contains quick-reacting components for removal of operationally caused contamination in the entire cooling circuit. The Product cleans the complete cooling system, dissolves and removes scale and improves the performance of valves, thermostats and water pumps.

ADVANTAGES

The major part of chemical energy that is bound in the fuel is converted into heat during the combustion process which must be dissipated. Therefore, a fully functional cooling system is of major importance for the operational liability of engines! Improved heating and cooling performance. Increases the operational liability of the cooling system and extends the life span of all aggregates.

CONTENT	PU	ART. NO.
250 ml	24 x 250 ml	Art. 09562
other sizes available on request		

PROPERTIES

Physical state	liquid
Color	colourless till light yellow
Density	1,01 g/cm ³
Flash point	>93 °C
Viscosity	1,2 mm ² /s (at 40 °C)

COMPATIBILITY

Compatible with all water-cooled, closed cooling systems.

SAFETY INSTRUCTIONS

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

DISPOSAL

Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.

GAT Gesellschaft für Kraftstoff - und
Automobiltechnologie mbH & Co. KG
Alt Saale 2
D - 07407 Uhlstädt-Kirchhasel

Phone: +49 (0) 36 72 48380-66
Fax: +49 (0) 36 72 48380-22
eMail: info@gat-international.de
web: www.gat-international.de

Geschäftsführerin | Managing Director
Dr. Gaby Urban – Moscow State Pedagogical University
Amtsgericht Gera HRB 503668
Ust.ID: DE297820562

MADE IN
GERMANY

revision status: 24.01.2023